

## RETAIL REFRIGERATED DISPLAY CASE CONDENSATE PUMPS

## PROACTIVE AI DIAGNOSTIC ALARM TECHNOLOGY

Al technology built into Hartell's new condensate pumps for retail refrigerated display cases offers proactive advance notice of potential system failure through instant non-intrusive visual and audible alarm notifications. These notifications provide instant fault diagnosis to help prevent water damage and system downtime.

Diagnostic Alerts:

- Discharge Line Partially Restriction Fault
- Discharge Line Fully Restricted Fault
- Discharge Line Open Fault
- Installation Fault
- Pump unable to handle discharge length / condensate production
- Pump Motor Failing or Faulty
- System Maintenance Monitor

No specialist commissioning or training for installation is required as Hartell's AI technology is self-calibrating and the maintenance monitor ensures the pumps are regularly maintained. Available in two models:

- > Vertical Model: HDP-AI-V1 (tank size of 2 gal/7.8 l) H: 5.91 in. (150mm), L: 18 in. (460mm), W: 4.72 in. (120mm)
- > Low Profile Model: HDP-AI-H1 (low profile of 2.44 in. tank size of 1 gal/4 l) H: 5.91 in. (150mm), L: 18 in. (460mm), W: 4.72 in. (120mm)
- 115 ft. (35m) pumping head
- 21 gal/hr (80 l/hr) flow rate
- BMS interface via volt-freeN/C-N/O contacts
- Built-in non-intrusive audible alarm
- Self-calibrating pump monitoring system using Hartell's Al
- Optional multifunctional remote visual indicator
- Input Voltage: 115V or 230V 50/60hz +/- 10%
- Inlet Connection: 2 in. (50mm) ID
- Outlet Connection: 1/2 in. (14mm) OD

